

CHEROKEE XJ

ARB DELUXE BULL BARS & WINCH BARS				
YEAR	MODEL	FEATURES	WINCHES	PART NO.
1997-02	WINCH BAR	AIRBAG APPROVED, RECESSED INDICATORS, TOW POINTS, BLACK	XD9000, M8000, M6000	3450080 ¹
1984-96	WINCH BAR	AIRBAG APPROVED, RECESSED INDICATORS, TOW POINTS, BLACK	XD9000, M8000, M6000	3450010 ¹

¹ MINOR MODIFICATIONS TO BAR MAY BE REQUIRED WHEN FITTING LARGE DIAMETER LAMPS.

IPF LIGHTING & ACCESSORIES	
YEAR	RECOMMENDED LIGHTING
1984-01	800XSD, 868CS, 968CSG, 820H ¹ (RECTANGULAR H4 HEADLAMP CONVERSION KIT, BULBS NOT INCLUDED)
1984-02	800XSD, 868CS, 968CSG

¹ IPF M002 HEADLIGHT UPGRADE HARNESS RECOMMENDED WHEN INSTALLING HIGH PERFORMANCE H4 BULBS

SAFARI SNORKEL		
YEAR	RECOMMENDED SNORKEL	PART NO.
2/95 TO 12/01	INLINE SIX, 4.0 LITRE, LEFT SIDE MOUNT	SS1195HF
TO 1/95	INLINE SIX, 4.0 LITRE, LEFT SIDE MOUNT	SS1100HF

REFER TO WWW.SAFARI4x4.COM.AU FOR DETAILS.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES		
YEAR	DESCRIPTION	PART NO.
DANA 44	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750003 ²
DANA 30	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750002 ^{1,2}
DANA 35	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750004 ²

¹ WILL NOT WORK WITH STOCK HEIGHT VEHICLES

² INTERNAL DIFF COVER MODIFICATIONS MAY BE NECESSARY WITH SOME R&P RATIOS IF CONTACT WITH COVER OCCURS

ARB ROOF RACKS		
YEAR	RECOMMENDED ROOF RACKS	PART NO.
1984-02	73 X 49" WITH MESH FLOOR	3800020M
	73 X 49" WITHOUT MESH FLOOR	3800020
	FITTING KIT FOR 73 X 49"	3700050
1984-02	43 X 49" WITH MESH FLOOR	3800030M
	43 X 49" WITHOUT MESH FLOOR	3800030
	FITTING KIT FOR 43 X 49"	3700060
	OPTIONAL WIND DEFLECTOR FOR 49" WIDE ROOF RACK	3700310
	OPTIONAL HI-LIFT JACK AND SHOVEL HOLDER FOR ARB ROOF RACK	K6202

THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT		
YEAR	DESCRIPTION	PART NO.
1985-01	THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT (W/FACTORY RACK)	TA50010
1985-01	THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT (W/O FACTORY RACK)	TA50050

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
1984-02	FRONT	STOCK/LIGHT LOAD (0-110LBS)	SPRING	1.75"	1	2930
		NITROCHARGER SPORT	SHOCK		2	60052
		NITROCHARGER	SHOCK		2	*N35/N35C
1984-02	FRONT	HEAVY LOAD (110-200LBS)	SPRING	1.50"	1	2930
		NITROCHARGER SPORT	SHOCK		2	60052
		NITROCHARGER	SHOCK		2	N35
1984-02	REAR	LIGHT LOAD	SPRING	2.0"	2	CS034RB
		NITROCHARGER SPORT	SHOCK		2	60053
		NITROCHARGER	SHOCK		2	*N36/N36C
1984-02	REAR	MEDIUM LOAD	SPRING	2.25"	2	CS034RA
		NITROCHARGER SPORT	SHOCK		2	60053
		NITROCHARGER	SHOCK		2	*N36/N36C
1984-02	REAR	MEDIUM LOAD	SPRING	2.75"	2	CS033RB
		NITROCHARGER SPORT	SHOCK		2	60053
		NITROCHARGER	SHOCK		2	*N36/N36C
1984-02	REAR	MEDIUM LOAD	SPRING	3.5"	2	CS033RA
		NITROCHARGER SPORT	SHOCK		2	60053
		NITROCHARGER	SHOCK		2	*N36/N36C
1984-02	REAR	HEAVY CONSTANT LOAD	SPRING	2.0"	2	CS035RA
		NITROCHARGER SPORT	SHOCK		2	60053
		REQUIRED FOR INSTALLATION	LEAF SPRING BUSHINGS			
		U BOLTS			4	OMEU60/57 ²
		T-CASE SPACER KIT			1	XJGK01
		STEERING DAMPER			1	OMESD40
	OPTIONAL	FRONT 10MM TRIM SPACER				OMEJGF10
		REAR EXTRA LEAF				D22XL ³
	ALSO AVAILABLE	FRONT EXTENDED LENGTH SHOCKS			2	N35L ⁴
		REAR EXTENDED LENGTH SHOCKS			2	N36L ⁴

¹ OE RUBBER LEAF SPRING BUSHINGS ARE USED TO ISOLATE ROAD NOISE. INSTALL ORIGINAL BUSHINGS FROM OE SPRINGS IF THEY ARE IN GOOD CONDITION, OR SOURCE NEW OE BUSHINGS FROM DEALERSHIP.

² OMEU60 SUITS DANA 35 TYPE AXLE. OMEU57 SUITS CHRYSLER 8.25" TYPE AXLE.

³ EXTRA LEAF CAN BE FITTED FOR HEAVIER CONSTANT LOAD CARRYING ABILITY.

⁴ N35L/N36L EXTENDED LENGTH SHOCKS ARE FOR 3-5" SUSPENSION LIFTS ONLY. MODIFIED BUMP STOP ARE REQUIRED.

* FIRMER SHOCK

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
ALL	FRONT	DANA 30	29.5 (1.16")	27	3.73 & UP	RD100
					3.54 & DN	RD101
				30	3.73 & UP	RD104
ALL	REAR	DANA 35, C-CLIP,	29.5 (1.16")	27	2.73-3.31	RD103
					3.54 & UP	RD102 ²
				30	3.54 & UP	RD105
ALL	REAR	CHRYSLER 8.25"	30.7 (1.21")	29	ALL	RD93 ¹
ALL	REAR	DANA 44	33.3 (1.31")	30	3.92 & UP	RD116
					3.73 & UP	RD117

¹PRE 1997 - 8.25" AXLE ASSEMBLIES W/27 SPLINE SHAFTS WILL ACCEPT NEWER 29 SPLINES SHAFTS IF RD93 IS FITTED

²SOME DANA 35'S 4.10 GEAR SETS, MAY REQUIRE A HIGH SPEED CARRIER AIR LOCKER (RD103)