

GRAND CHEROKEE ZJ

ARB DELUXE BULL BARS & WINCH BARS				
YEAR	MODEL	FEATURES	WINCHES	PART NO.
1993-98	WINCH BAR	AIRBAG APPROVED, RECESSED INDICATORS, TOW POINTS, BLACK	HS9500, XD9000, M8000, M6000	3450060

IPF LIGHTING & ACCESSORIES	
YEAR	RECOMMENDED LIGHTING
1993-98	ARB INTENSITY LED, 800XSD, 901XSD, 901XSS, 900HIDD, 900HIDS, 900DB, 868CS, 968CSG

SAFARI SNORKEL		
YEAR	RECOMMENDED SNORKEL	PART NO.
1993-98	ALL V8 MODELS, 4.0 I6 MODELS ¹	SS1120HF

¹ 1993-95 INLINE 6 (4.0L) MODELS REQUIRE THE RELOCATION OF THE PCM AND ADDITIONAL INSTALLATION STEPS.

OLD MAN EMU SUSPENSION SYSTEMS						
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
4.0L 6CYL	FRONT	STOCK.LIGHT LOAD (0-80LBS)	SPRING	1.0"	1	2931
		NITROCHARGER SPORT	SHOCK		2	60092
			SHOCK		2	N39
4.0L 6CYL	FRONT	MEDIUM LOAD (80-160LBS)	SPRING	.75"	1	2930
		NITROCHARGER SPORT	SHOCK		2	60092
			SHOCK		2	N39
5.2L V8	FRONT	STOCK.LIGHT LOAD (0-90LBS)	SPRING	1.0"	1	2934
		NITROCHARGER SPORT	SHOCK		2	60092
			SHOCK		2	N39
5.2L V8	FRONT	HEAVY LOAD (90-180LBS)	SPRING	.75"	1	2934
		NITROCHARGER SPORT	SHOCK		2	60092
			SHOCK		2	N39
ALL	REAR	MEDIUM LOAD	SPRING	1.0"	1	2940
		NITROCHARGER SPORT	SHOCK		2	60093
ALL	REAR	HEAVY CONSTANT LOAD (220LBS +)	SPRING	.75"	1	2943
		NITROCHARGER SPORT	SHOCK		2	60093
	REQUIRED	STEERING DAMPER			1	OMESD40 ¹
		STEERING DAMPER			1	OMESD48 ¹
	OPTIONAL	FRONT 10MM TRIM PACKER				OMEJGF10
		REAR 10MM TRIM PACKER				OMEJGR10

¹ FOR STANDARD APPLICATIONS, USE OMESD40. FOR APPLICATIONS NEEDING FIRMER VALVING, USE OMESD48

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1993-98	FRONT	DANA 30	29.5 (1.16")	27	3.73 & UP	RD100 ¹
				27	3.54 & DN	RD101 ¹
			1.31"(33.3)	30	3.73 & UP	RD104
1993-98	REAR	DANA 35, C-CLIP, XJ, YJ, ZJ, TJ, WJ	29.5 (1.16")	27	2.73-3.31	RD103 ²
					3.54 & UP	RD102 ^{2,3}
			1.31" (33.3)	30	3.54 & UP	RD105
		DANA 44A	1.31" (33.3)	30	ALL	RD226 ¹

¹ QUADRADRIE TRACTION CONTROL VEHICLES REQUIRE NON-QUADRADRIE AXLE SHAFT REPLACEMENTS FOR AIR LOCKER INSTALLATION.

² NEWER OEM DANA 35 & DANA 44 GEAR RINGS HAVE 7/16" BOLTS. FLANGE HOLES OF THE AIR LOCKER MUST BE REAMED LARGER TO SUIT.

³ SOME DANA 35'S 4.10 GEAR SETS, MAY REQUIRE A HIGH SPEED CARRIER AIR LOCKER. (RD103)

ARB AIR LOCKER DIFFERENTIAL COVERS

DIFFERENTIAL	DESCRIPTION	PART NO.
DANA 30	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750002 ^{1,2}
DANA 35	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750004 ²

¹ WILL NOT WORK WITH STOCK HEIGHT VEHICLES

² INTERNAL DIFF COVER MODIFICATIONS MAY BE NECESSARY WITH SOME R&P RATIOS IF CONTACT WITH COVER OCCURS