

WRANGLER JK (2 DOOR)

ARB DELUXE BULL BARS & WINCH BARS				
YEAR	MODEL	FEATURES	WINCHES	PART NO.
2007-12	WINCH BUMPER	AIR BAG APPROVED, RETAINS THE FACTORY FOG LAMPS, URETHANE BUFFERS, RECOVERY POINTS, HI-LIFT JACK POINTS, AUXILIARY LIGHT MOUNT PROVISIONS	WARN 6-9500LBS, 9.5TI, WARN POWERPLANT	3450220 ^{1,2}
2007-12	ROCKBAR	RECOVERY POINTS, HI-LIFT JACK POINTS, AUXILIARY LIGHT MOUNT PROVISIONS	WARN 6-9500LBS, 9.5TI, WARN POWERPLANT	3450210

¹ IF NOT FITTING FACTORY FOG LAMPS, ORDER PART # 3550030 (FOGLIGHT INSERT COVER) TO COMPLETE INSTALLATION

² IF NOT FITTING WINCH, ORDER PART # 3550040 (TOP PAN COVER) TO COMPLETE INSTALLATION

IPF LIGHTING & ACCESSORIES	
YEAR	RECOMMENDED LIGHTING
2007-12	800XSD, 900XSD, 900XSS, 900HIDD, 900HIDS, 930S/R, 868CS, 968CSG
2007-12	920HJJK - H4 HEADLIGHT CONVERSION WITH 60/55W BULBS
2007-12	920HJKTJ - H4 HEADLIGHT CONVERSION WITHOUT BULBS

SAFARI SNORKEL		
YEAR	RECOMMENDED SNORKEL	PART NO.
2007-11	3.8L V6 GAS ENGINE (LEFT HAND DRIVE)	SS1066HF

ARB SIDE RAILS/ROCK SLIDERS/STEPS		
YEAR	DESCRIPTION	PART NO.
2007-12	ROCK SLIDERS	4450200

ARB REAR PROTECTION BUMPERS		
YEAR	TYPE	PART NO.
2007-12	REAR BUMPER ASSEMBLY, RECOVERY POINTS, BLACK	5650200 ^{1,2,3}
	REAR BUMPER ASSEMBLY, OPTIONAL TIRE CARRIER ⁴ , RECOVERY POINTS, BLACK	5650350 ^{3,4}
	OPTIONAL SPARE TIRE CARRIER	5750300 ^{4,5}
	OPTIONAL IPF REVERSE LIGHT	8161

¹ NON SWING OUT, TIRE MOUNTS IN FACTORY POSITION

² ACCOMODATES UP TO A 35" TIRE

³ UTILIZES FACTORY TOW PACKAGE

⁴ OPTIONAL SPARE TIRE CARRIER PART NO 5750300 WILL ONLY WORK IN COMBINATION WITH BUMPER PART NUMBER 5650350

⁵ WILL WORK WITH UP TO A 37" TIRE. MODIFICATION TO 3RD BRAKE LIGHT MAY BE REQUIRED TO FIT 37" SPARE TIRE.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES						
YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
2007-12	FRONT	DANA 30	29.5 (1.16")	27	3.73 & UP	RD100
				27	3.54 & DN	RD101
		DANA 44 - RUBICON ONLY	38.1 (1.50")	35	ALL ⁴	RD157 ^{2,3,4}
2007-12	REAR	DANA 44	33.3 (1.31")	30	ALL	RD117 ¹
				35	ALL	RD147 ^{1,2}
		DANA 44 - RUBICON ONLY	38.1 (1.50")	35	ALL ⁴	RD157 ^{2,3,4}

¹ WILL NOT FIT RUBICON MODELS

² AFTERMARKET AXLE SHAFTS REQUIRED, NOT SUPPLIED BY ARB

³ WILL WORK WITH JK RUBICON DANA 44 HOUSING

⁴ WILL WORK WITH JK RUBICON DANA 44 GEARS ONLY

ARB AIR LOCKER DIFFERENTIAL COVERS		
DIFFERENTIAL	DESCRIPTION	PART NO.
DANA 44	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750003*
DANA 30	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750002*
DANA 35	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750004*

* INTERNAL DIFF COVER MODIFICATIONS MAY BE NECESSARY WITH SOME R&P RATIOS IF CONTACT WITH COVER OCCURS



OLD MAN EMU SUSPENSION SYSTEMS						
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
2007-12	COMPLETE KITS	GAS - STOCK/LIGHT LOAD (0-90LBS)	KIT	2-2.25"	1	OMEJK2DLKS ⁵
		GAS - HEAVY LOAD (90-180LBS)	KIT	2-2.25"	1	OMEJK2DHKS ⁵
		GAS - STOCK/LIGHT LOAD (0-90LBS)	KIT	2-2.25"	1	OMEJK2DLK ⁶
		GAS - HEAVY LOAD (90-180LBS)	KIT	2-2.25"	1	OMEJK2DHK ⁶
2007-12	FRONT	GAS - STOCK/LIGHT LOAD (0-90LBS)	SPRING	2"	1	2615
		NITROCHARGER SPORT	SHOCK		2	60066
		NITROCHARGER	SHOCK		2	*N196/N211
2007-12	FRONT	GAS - HEAVY LOAD (90-180LBS)	SPRING	2"	1	2616
		NITROCHARGER SPORT	SHOCK		2	60066
		NITROCHARGER	SHOCK		2	*N196/N211
2007-12	REAR	GAS - MEDIUM LOAD	SPRING	2.25"	1	2617
		NITROCHARGER SPORT	SHOCK		2	60067
		NITROCHARGER	SHOCK		2	*N198/N212
2007-12	REAR	GAS - HEAVY CONSTANT LOAD (300LBS)	SPRING	2.25"	1	2618
		NITROCHARGER SPORT	SHOCK		2	60067
		NITROCHARGER	SHOCK		2	*N198/N212
OPTIONAL		STEERING DAMPER			1	OMESD48 ⁷
		STEERING DAMPER RELOCATION BRACKET			1	FK50 ⁷
		PANHARD ROD EXTENSION BRACKET KIT LHD			1	FK37 ²
		PANHARD ROD EXTENSION BRACKET KIT RHD			1	FK39 ²
		FRONT TRIM SPACER 10MM			1	OMEJKPF10 ¹
		REAR TRIM SPACER 10MM			1	OMEJKPR10 ¹
		NITROCHARGER SPORT FRONT EXTENDED LENGTH SHOCK			2	60066L ³
		NITROCHARGER FRONT EXTENDED LENGTH SHOCK			2	N196L ³
		NITROCHARGER SPORT REAR EXTENDED LENGTH SHOCK			2	60067L ³
		NITROCHARGER REAR EXTENDED LENGTH SHOCKS			2	N198L ³
		BUMP STOP EXTENSIONS			1	FK40 ⁴

¹ DO NOT FIT MORE THAN ONE TRIM SPACER PER COIL SPRING

² FITMENT OF PANHARD ROD EXTENSION BRACKET IS NOT MANDATORY, BUT FITMENT WILL IMPROVE THE RIDE

³ EXTENDED LENGTH SHOCKS ARE FOR 3-5" SUSPENSION LIFTS ONLY AND ARE NOT INTENDED FOR USES WITH ANY OLD MAN EMU SYSTEMS. MODIFIED BUMP STOPS ARE REQUIRED.

⁴ REQUIRED IF FITTING 35" TIRES

⁵ KIT CONTAINS NITROCHARGER SPORT SHOCKS

⁶ KIT CONTAINS STANDARD NITROCHARGER SHOCKS

⁷ FITMENT OF OMESD48 STEERING DAMPER REQUIRES RELOCATION BRACKET PART NUMBER FK50

* FIRMER SHOCK