

### ARB DELUXE BULL BARS & WINCH BARS

YEAR	MODEL	FEATURES	WINCHES	PART NO.
2001-2006	WINCH BAR	SRS AIRBAG APPROVED, RECESSED INDICATORS, BLACK	HS9500, XD9000, M8000, M6000	3446060
TO 8/2001	WINCH BAR	FOR NON-SRS AIRBAG MODELS, RECESSED INDICATORS, BLACK	HS9500, XD9000, M8000, M6000	3446030

### IPF LIGHTING & ACCESSORIES

YEAR	RECOMMENDED LIGHTING
1996-05	800XSD, 868CS

### SAFARI SNORKEL

YEAR	RECOMMENDED SNORKEL	PART NO.
1996-06	2.8L DIESEL/TURBO DIESEL MODELS	SS650R

REFER TO [WWW.SAFARI4x4.COM.AU](http://WWW.SAFARI4x4.COM.AU) FOR DETAILS.

### OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
1996-2005	FRONT	MEDIUM LOAD (110LBS TO GVW)	TORSION		1	303006 <sup>1</sup>
		MH MODELS	SHOCK		2	60051
		MK MODELS	SHOCK		2	60040
1996-2005	REAR	MEDIUM LOAD (0LBS TO GVW)	SPRING	1.50"	2	CS022R <sup>2</sup>
		MH MODELS	SHOCK		2	60058
		MK MODELS	SHOCK		2	60050
		HEAVY CONSTANT (440LBS TO GVW)	SPRING	1.50"	2	CS023R <sup>2</sup>
		MH MODELS	SHOCK		2	60058
		MK MODELS	SHOCK		2	60050
		REQ'D FOR INSTALLATION	LEAF SPRING BUSHING KIT			2
	U BOLTS			4	OMEU57	
	ANTI-INVERSION KIT			1	FK30 <sup>3</sup>	
	GREASABLE SHACKLE KIT			1	OMEGB16	

\* FIRMER SHOCK

<sup>1</sup> ADJUST FRONT TORSION BAR FOR ADDITIONAL HEIGHT AFTER INSTALLING REAR SPRINGS. SET RIDE HEIGHT TO 1/3 UPPER BUMP STOP CLEARANCE AND 2/3 LOWER BUMP STOP CLEARANCE.

<sup>2</sup> OME LEAF SPRINGS CAN ONLY BE INSTALLED WITH OME BUSH KITS IN THIS APPLICATION.

<sup>3</sup> FK30 ANTI-INVERSION KIT IS A MANDATORY FITMENT IN THIS APPLICATION.

\*\* BE SURE TO SELECT CORRECT SHOCKS FOR EITHER MH OR MK MODELS

### ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1991 ON	FRONT	IFS, 28 SPLINE		28	ALL	RD110 <sup>2</sup>
1987-95	REAR	LARGE <sup>1</sup> DIFFERENTIAL DISC BRAKE	30.5 (1.20")	28	ALL	RD158
		LARGE <sup>1</sup> DIFFERENTIAL DRUM BRAKE	30.5 (1.20")	28	ALL	RD162

<sup>1</sup> LARGE DIFFERENTIAL HAS A CROWN WHEEL SPIGOT DIAMETER OF 145MM.

<sup>2</sup> WILL NOT FIT PAJERO/MONTERO 3.0L AUTOMATIC