

ARB DELUXE BULL BARS & WINCH BARS

| YEAR | MODEL | FEATURES | WINCHES | PART NO. |
|---------|-----------|--|---------------|----------|
| 1991-97 | WINCH BAR | RECESSED INDICATORS, TOW POINTS, BLACK | XD9000, M8000 | 3438050 |

IPF LIGHTING & ACCESSORIES

| YEAR | RECOMMENDED LIGHTING |
|---------|--------------------------------------|
| 1991-97 | 800XSD, 900XS, 900HID, 868CS, 968CSG |

SAFARI SNORKEL

| YEAR | RECOMMENDED SNORKEL | PART NO. |
|---------|------------------------------------|----------|
| 1986-97 | D21, 2.7L, DIESEL, LEFT SIDE MOUNT | SS700HF |

REFER TO WWW.SAFARI4x4.COM.AU FOR DETAILS.

OLD MAN EMU SUSPENSION SYSTEMS

| MODEL | LOCATION | DESCRIPTION | TYPE | LIFT | QUANTITY | PART NO. |
|------------|------------------------|------------------------------|---------|------|----------|---------------------|
| D21 MODELS | FRONT | MEDIUM LOAD (OVER 110LBS) | TORSION | | 1 | 303008 ¹ |
| | | NITROCHARGER SPORT | SHOCK | | 2 | 60021 |
| | | NITROCHARGER | SHOCK | | 2 | N58 ² |
| | REAR | MEDIUM LOAD (0LBS TO GVW) | SPRING | 1.0" | 2 | CS030R |
| | | NITROCHARGER SPORT | SHOCK | | 2 | 60035 |
| | | NITROCHARGER | SHOCK | | 2 | N56 |
| | | HEAVY CONSTANT LOAD (800LBS) | SPRING | 1.0" | 2 | CS031R |
| | | NITROCHARGER SPORT | SHOCK | | 2 | 60035 |
| | | NITROCHARGER | SHOCK | | 2 | N59 |
| | REQ'D FOR INSTALLATION | STEERING DAMPER | | | 1 | OMESD35 |
| | | SPRING BUSHING KIT | | | 2 | OMESB81 |
| | | UBOLTS | | | 4 | OMEU63 |

¹ ADJUST FRONT TORSION BAR FOR ADDITIONAL HEIGHT AFTER INSTALLING REAR SPRINGS. SET RIDE HEIGHT TO 1/3 UPPER BUMP STOP CLEARANCE AND 2/3 LOWER BUMP STOP CLEARANCE.

² IT MAY BE NECESSARY TO SLIGHTLY INCREASE THE CLEARANCE IN THE FRONT WISHBONE TO ALLOW SHOCK ABSORBER TO FIT. DO NOT MODIFY SHOCK ABSORBER.
FIRMER SHOCK.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

| YEAR | AXLE | DESCRIPTION | SHAFT | SPLINE | RATIO | PART NO. |
|---------|-------|--------------------------|--------------|--------|-------|----------------------|
| 1986 ON | FRONT | R180A, 4 CYL. | 27.8 (1.09") | 27 | ALL | N/A |
| | | R200A, 6 CYL. | 30.4 (1.20") | 29 | ALL | RD107 |
| 1986 ON | REAR | H233B, 31 SPLINE, 6 CYL. | 32.4 (1.20") | 31 | ALL | RD136 ² |
| | | H233B, 33 SPLINE, 6 CYL. | 33.3 (1.31") | 33 | ALL | RD135 ² |
| 1986-97 | REAR | C200, 29 SPLINE, 4 CYL. | 30.4 (1.20") | 29 | ALL | RD107 ^{1,2} |

¹ ONLY SUITABLE FOR DIFFERENTIALS WITH 12MM CROWN WHEEL BOLTS.

² REFER TO DEALER OR CHECK SPLINE COUNT TO DETERMINE AXLE TYPE.