

## PATROL GQ

### ARB DELUXE BULL BARS & WINCH BARS

YEAR	MODEL	FEATURES	WINCHES	PART NO.
TO 1992	BULL BAR	NON WINCH		3216080 <sup>1</sup>
ALL	WINCH BAR		9000LB, 12XE	3416110 <sup>1,2</sup>

<sup>1</sup> COIL SPRING MODELS

<sup>2</sup> KIT PART # 3500050 REQUIRED TO INSTALL 8/9000LB WINCH MODELS

### IPF LIGHTING & ACCESSORIES

YEAR	RECOMMENDED LIGHTING
ALL	800XSD, 900XS, 900HID
ALL	920HJKTJ - 7" ROUND H4 HEADLIGHT CONVERSION KIT W/O BULBS

### ARB ROCK SLIDERS/SIDE RAILS/STEPS

YEAR	MODEL	DESCRIPTION	PART NO.
ALL	SWB	SIDE RAILS AND STEPS	4416040
ALL	LWB	SIDE RAILS AND STEPS	4416020

### SAFARI SNORKEL

YEAR	RECOMMENDED SNORKEL	PART NO.
1988 ON	TB42E, 4.2L, GAS, LEFT HAND MOUNT	SS10HFVPC

REFER TO [WWW.SAFARI4X4.COM.AU](http://WWW.SAFARI4X4.COM.AU) FOR DETAILS.

### ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1988-98	FRONT	H233B	32 (1.26")	31	ALL	RD136
	REAR	H233B, REAR DISC BRAKES	33.3 (1.31")	33	ALL	RD135
		H233B, REAR DRUM BRAKES	33.3 (1.31")	33	ALL	RD135
		H260, LEAF SPRUNG CAB CHASSIS & UTILITY	38.4 (1.51")	37	ALL	RD70

<sup>1</sup> ONLY SUITABLE FOR DIFFERENTIALS WITH 12MM RING GEAR BOLTS.

<sup>2</sup> REFER TO DEALER OR CHECK SPLINE COUNT TO DETERMINE AXLE TYPE.

### ARB ROOF RACKS

YEAR	DESCRIPTION	PART NO.
GQ LWB AND SWB <sup>1</sup>	87X49" STEEL RACK WITH MESH FLOOR	3800010M
	87X49" STEEL RACK WITHOUT MESH FLOOR	3800010
	87X49" ALLOY RACK WITH MESH FLOOR	4900010M
	87X49" STEEL TOURING RACK FOR ROOF TOP TENT	3800200
	FITTING KIT FOR 87X49" RACKS (ALLOY & STEEL)	3700050
	73X49" STEEL WITH MESH FLOOR	3800020M
	73X49" STEEL WITHOUT MESH FLOOR	3800020
	FITTING KIT FOR 73X49" RACKS	3700050
	43X49" STEEL RACK WITH MESH FLOOR	3800030M
	FITTING KIT FOR 43X49" RACKS	3700060
	WIND DEFLECTOR FOR 49" WIDE ROOF RACK	3700310
	HI-LIFT JACK AND SHOVEL HOLDER FOR ARB ROOF RACK	K6202

<sup>1</sup> USE 43" X 49" RACK FOR SWB VEHICLES WITH STEEL ROOF

### OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
GQ Y60 LWB, 4.2L DIESEL & GAS	FRONT	LIGHT LOAD TO 110LBS	SPRING	2"	1	2975	
		NITROCHARGER SPORT	SHOCK		2	60012	
		NITROCHARGER	SHOCK		2	N23F	
	REQ'D FOR INSTALLATION	STEERING DAMPER				1	OMESD36 <sup>5</sup>
		STEERING DAMPER				1	OMESD34 <sup>5</sup>
		CASTER KIT				1	OMECA77B <sup>2</sup>
		TRIM PACKER					OMEGQPF05 <sup>1</sup>
		TRIM PACKER					OMEGQPF10 <sup>1</sup>
GQ Y60 LWB, 4.2L DIESEL & GAS	FRONT	LOAD 110 - 240LBS	SPRING	2"	1	2976	
		NITROCHARGER SPORT	SHOCK		2	60013	
		NITROCHARGER	SHOCK		2	*N21/N23F	
	REQ'D FOR INSTALLATION	STEERING DAMPER				1	OMESD36 <sup>5</sup>
		STEERING DAMPER				1	OMESD34 <sup>5</sup>
		CASTER KIT				1	OMECA77B <sup>2</sup>
		TRIM PACKER					OMEGQPF05 <sup>1</sup>
		TRIM PACKER					OMEGQPF10 <sup>1</sup>
GQ Y60 LWB, 4.2L DIESEL & GAS	FRONT	LOW HEIGHT TO 110LBS	SPRING	1"	2	2974	
		NITROCHARGER SPORT	SHOCK		2	60012	
		NITROCHARGER	SHOCK		2	N21	
	REQ'D FOR INSTALLATION	STEERING DAMPER				1	OMESD36 <sup>5</sup>
		STEERING DAMPER				1	OMESD34 <sup>5</sup>
		CASTER KIT				1	OMECA77B <sup>2</sup>
		TRIM PACKER					OMEGQPF05 <sup>1</sup>
		TRIM PACKER					OMEGQPF10 <sup>1</sup>
ALL	REAR	LIGHT TO MEDIUM LOADS	SPRING	1.5"	1	2GQ02C	
		NITROCHARGER SPORT	SHOCK		2	60014	
		NITROCHARGER	SHOCK		2	N22F	
	REQ'D FOR INSTALLATION	TRIM PACKER					OMEGQPF05 <sup>1</sup>
		TRIM PACKER					OMEGQPF10 <sup>1</sup>
	ALL	REAR	MEDIUM LOAD TO GWV	SPRING	2"	2	OMEGQ2AM
			NITROCHARGER SPORT	SHOCK		2	60014
NITROCHARGER			SHOCK		2	N22F	
REQ'D FOR INSTALLATION		GEARBOX PACKER KIT				1	GQGK01 <sup>3</sup>
		TRIM PACKER					OMEGQPR05 <sup>1</sup>
		TRIM PACKER					OMEGQPR10 <sup>1</sup>
ALL		REAR	LIGHT TO MEDIUM LOADS	SPRING	1.5"	1	2GQ02C
			NITROCHARGER SPORT	SHOCK		2	60014
	NITROCHARGER		SHOCK		2	N22F	
	REQ'D FOR INSTALLATION	TRIM PACKER					OMEGQPF05 <sup>1</sup>
		TRIM PACKER					OMEGQPF10 <sup>1</sup>
	ALL	REAR	MEDIUM LOAD TO GWV	SPRING	2"	2	OMEGQ2AM
			NITROCHARGER SPORT	SHOCK		2	60014
NITROCHARGER			SHOCK		2	N22F	

\* CONTINUED ON NEXT PAGE

## PATROL GQ

OLD MAN EMU SUSPENSION SYSTEMS						
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
ALL	REQ'D FOR INSTALLATION	GEARBOX PACKER KIT			1	GQGK01 <sup>3</sup>
		TRIM PACKER				OMEGQPR05 <sup>1</sup>
		TRIM PACKER				OMEGQPR10 <sup>1</sup>
ALL	REAR	CONSTANT 440LBS TO GVW	SPRING	2"	1	2GQ02J
		NITROCHARGER SPORT	SHOCK		2	60015
		NITROCHARGER	SHOCK		2	*N29/N22F
	REQ'D FOR INSTALLATION	GEARBOX PACKER KIT			1	GQGK01 <sup>3</sup>
		TRIM PACKER				OMEGQPR05 <sup>1</sup>
		TRIM PACKER				OMEGQPR10 <sup>1</sup>

- <sup>1</sup> COIL TRIM PACKERS MAY BE REQUIRED TO TRIM VEHICLE TO A MAXIMUM OF .59" PER COIL. PACKERS MUST BE INSTALLED ON THE TOP ON REAR COILS AND TO THE BOTTOM ON FRONT COILS. PART No. OMEGQPF10 & OMEGQPR10 = .39". PART No. OMEGQPR10 & OMEGQPR05 = .20"
- <sup>2</sup> OMECA77B CASTER KIT WILL INCREASE CASTER ANGLE BY 2°. CASTER ANGLE WILL BE AFFECTED WHEN RAISING VEHICLE. CHECK MANUFACTURER'S SPECIFICATIONS TO DETERMINE IF OMECA77B IS REQUIRED.
- <sup>3</sup> GEARBOX PACKER KIT IS DESIGNED TO SPACE DOWN THE GEARBOX CROSS MEMBER FROM THE CHASSIS TO REDUCE TAIL SHAFT FLANGE ANGLE THEREBY REDUCING DRIVELINE VIBRATION.
- <sup>5</sup> OMESD36 FITS 8/89 MODELS ONWARDS. OMESD34 FITS PRE 8/89 MODELS.

OLD MAN EMU SUSPENSION SYSTEMS						
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
GQ Y60, 3L PETROL & 2.8 TURBO DIESEL, SWB & LWB	FRONT	LIGHT LOAD TO 110LBS	SPRING	2"	2	2974
		NITROCHARGER SPORT	SHOCK		2	60012
		SHOCK	SHOCK		2	N23F
	REQ'D FOR INSTALLATION	STEERING DAMPER			1	OMESD36
		CASTER KIT			1	OMECA77B <sup>2</sup>
		TRIM PACKER				OMEGQPF05 <sup>1</sup>
		TRIM PACKER			OMEGQPF10 <sup>1</sup>	
GQ Y60, 3L PETROL & 2.8 TURBO DIESEL, SWB & LWB	FRONT	LOAD 110 - 240LBS	SPRING	2"	1	2972
		NITROCHARGER SPORT	SHOCK		2	60013
		NITROCHARGER	SHOCK		2	*N21/N23F
	REQ'D FOR INSTALLATION	STEERING DAMPER			1	OMESD36
		CASTER KIT			1	OMECA77B <sup>2</sup>
		TRIM PACKER				OMEGQPF05 <sup>1</sup>
		TRIM PACKER			OMEGQPF10 <sup>1</sup>	
GQ Y60, 3L PETROL & 2.8 TURBO DIESEL, SWB & LWB	REAR	LIGHT TO MEDIUM LOAD	SPRING	1"	1	2GQ02CM
		NITROCHARGER SPORT	SHOCK		2	60014
		NITROCHARGER	SHOCK		2	N22F
	REQ'D FOR INSTALLATION	TRIM PACKER				OMEGQPR05 <sup>1</sup>
		TRIM PACKER				OMEGQPR10 <sup>1</sup>
GQ Y60, 3L PETROL & 2.8 TURBO DIESEL, SWB & LWB	REAR	MEDIUM LOAD TO GVW	SPRING	1.5"	1	2GQ02C
		NITROCHARGER SPORT	SHOCK		2	60014
		NITROCHARGER	SHOCK		2	N22F
	REQ'D FOR INSTALLATION	TRIM PACKER				OMEGQPR05 <sup>1</sup>
		TRIM PACKER				OMEGQPR10 <sup>1</sup>
		GEARBOX PACKER KIT			1	GQGK01 <sup>3</sup>

\* CONTINUED ON NEXT PAGE

### OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
GQ Y60, 3L(P) & 2.8 TURBO(D), SWB & LW	REAR	CONSTANT 440LBS TO GVW	SPRING	2"	1	2GQ02J	
		NITROCHARGER SPORT	SHOCK		2	60015	
		NITROCHARGER	SHOCK		2	*N29/N22F	
	INSTALLATION	TRIM PACKER					OMEGQPR05 <sup>1</sup>
		TRIM PACKER					OMEGQPR10 <sup>1</sup>
		GEARBOX PACKER KIT			1		GQGK01 <sup>3</sup>

<sup>1</sup> COIL TRIM PACKERS MAY BE REQUIRED TO TRIM VEHICLE TO A MAXIMUM OF .59" PER COIL. PACKERS MUST BE INSTALLED ON THE TOP ON REAR COILS AND TO THE BOTTOM ON FRONT COILS. PART No. OMEGQPF10 & OMEGQPR10 = .39". PART No. OMEGQPR10 & OMEGQPR05 = .20"

<sup>2</sup> OMECA77B CASTER KIT WILL INCREASE CASTER ANGLE BY 2°. CASTER ANGLE WILL BE AFFECTED WHEN RAISING VEHICLE. CHECK MANUFACTURER'S SPECIFICATIONS TO DETERMINE IF OMECA77B IS REQUIRED.

<sup>3</sup> GEARBOX PACKER KIT IS DESIGNED TO SPACE DOWN THE GEARBOX CROSS MEMBER FROM THE CHASSIS TO REDUCE TAIL SHAFT FLANGE ANGLE THEREBY REDUCING DRIVELINE VIBRATION.

### OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
GQ Y60 ALL 4.2 SWB	FRONT	LIGHT LOAD TO 100LBS	SPRING	2"	1	2975	
		NITROCHARGER SPORT	SHOCK		2	60012	
		NITROCHARGER	SHOCK		2	N23F	
	REQ'D FOR INSTALLATION	TRIM PACKER					OMEGQPF05 <sup>1</sup>
		TRIM PACKER					OMEGQPF10 <sup>1</sup>
		STEERING DAMPER			1		OMESD36 <sup>5</sup>
		STEERING DAMPER			1		OMESD34 <sup>5</sup>
		CASTER KIT			1	OMECA77B <sup>2</sup>	
GQ Y60 ALL 4.2 SWB	FRONT	HEAVY LOAD 110 TO 240LBS	SPRING	2"	1	2976	
		NITROCHARGER SPORT	SHOCK		2	60013	
		NITROCHARGER	SHOCK		2	N22F	
	REQ'D FOR INSTALLATION	TRIM PACKER					OMEGQPF05 <sup>1</sup>
		TRIM PACKER					OMEGQPF10 <sup>1</sup>
		CASTER KIT			1		OMECA77B <sup>2</sup>
GQ Y60 ALL 4.2 SWB	FRONT	LOW HEIGHT 110LBS LOAD	SPRING	1"	1	2974	
		NITROCHARGER SPORT	SHOCK		2	60012	
		NITROCHARGER	SHOCK		2	*N21/N23F	
	REQ'D FOR INSTALLATION	TRIM PACKER					OMEGQPF05 <sup>1</sup>
		TRIM PACKER					OMEGQPF10 <sup>1</sup>
		STEERING DAMPER			1		OMESD36 <sup>5</sup>
		STEERING DAMPER			1		OMESD34 <sup>5</sup>
		CASTER KIT			1		OMECA77B <sup>2</sup>
	REAR	LIGHT TO MEDIUM LOAD		SPRING	1"	1	2GQ02CM
			NITROCHARGER SPORT	SHOCK		2	60014
			NITROCHARGER	SHOCK		2	N22F
REQ'D FOR INSTALLATION		TRIM PACKER					OMEGQPR05 <sup>1</sup>
		TRIM PACKER					OMEGQPR10 <sup>1</sup>
		GEARBOX PACKER KIT			1		GQGK01 <sup>3</sup>

\* CONTINUED ON THE NEXT PAGE

## PATROL GQ

OLD MAN EMU SUSPENSION SYSTEMS								
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.		
GQ Y60 ALL 4.2 SWB	REAR	MEDIUM LOAD TO GWV	SPRING	1.5"	1	2GQ02CM		
		NITROCHARGER SPORT	SPRING		2	60014		
		NITROCHARGER	SHOCK		2	N22F		
		REQ'D FOR INSTALLATION	TRIM PACKER				OMEGQPR05 <sup>1</sup>	
		TRIM PACKER					OMEGQPR10 <sup>1</sup>	
			GEARBOX PACKER KIT			1	GQGK01 <sup>3</sup>	
	REAR	CONSTANT 440LBS TO GWV	SPRING	1.5"	1	2GQ02G		
		NITROCHARGER SPORT	SHOCK		2	60015		
		NITROCHARGER	SHOCK		2	N22F		
		REQ'D FOR INSTALLATION	TRIM PACKER				OMEGQPR05 <sup>1</sup>	
TRIM PACKER						OMEGQPR10 <sup>1</sup>		
		GEARBOX PACKER KIT			1	GQGK01 <sup>3</sup>		

<sup>1</sup> COIL TRIM PACKERS MAY BE REQUIRED TO TRIM VEHICLE TO A MAXIMUM OF .59" PER COIL. PACKERS MUST BE INSTALLED ON THE TOP ON REAR COILS AND TO THE BOTTOM ON FRONT COILS. PART No. OMEGQPF10 & OMEGQPR10 = .39". PART No. OMEGQPR10 & OMEGQPR05 = .20"

<sup>2</sup> OMECA77B CASTER KIT WILL INCREASE CASTER ANGLE BY 2°. CASTER ANGLE WILL BE AFFECTED WHEN RAISING VEHICLE. CHECK MANUFACTURER'S SPECIFICATIONS TO DETERMINE IF OMECA77B IS REQUIRED.

<sup>3</sup> GEARBOX PACKER KIT IS DESIGNED TO SPACE DOWN THE GEARBOX CROSS MEMBER FROM THE CHASSIS TO REDUCE TAIL SHAFT FLANGE ANGLE THEREBY REDUCING DRIVELINE VIBRATION.

<sup>5</sup> OMESD36 FITS 8/89 MODELS ONWARDS. OMESD34 FITS PRE 8/89 MODELS.

OLD MAN EMU SUSPENSION SYSTEMS								
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.		
GQ Y60 CAB CHASSIS COIL SPRING MODELS	FRONT	LIGHT LOAD TO 110LBS	SPRING	2"	1	2975		
		NITROCHARGER SPORT	SHOCK		2	60012		
		NITROCHARGER	SHOCK		2	N23F		
		REQ'D FOR INSTALLATION	TRIM PACKER				OMEGQPF05 <sup>1</sup>	
		TRIM PACKER					OMEGQPF10 <sup>1</sup>	
			STEERING DAMPER			1	OMESD36	
			CASTER KIT			1	OMECA77B <sup>2</sup>	
	FRONT	HEAVY LOAD 110 TO 240LBS	SPRING	2"	1	2976		
		NITROCHARGER SPORT	SHOCK		2	60013		
		NITROCHARGER	SHOCK		2	N21		
REQ'D FOR INSTALLATION		TRIM PACKER				OMEGQPF05 <sup>1</sup>		
TRIM PACKER						OMEGQPF10 <sup>1</sup>		
		STEERING DAMPER			1	OMESD36		
		CASTER KIT			1	OMECA77B <sup>2</sup>		
REAR	MEDIUM LOAD TO GWV	SPRING	1.5"	1	2GQ02C			
	NITROCHARGER SPORT	SHOCK		2	60014			
	NITROCHARGER	SHOCK		2	N22F			
	REQ'D FOR INSTALLATION	TRIM PACKER				OMEGQPR05 <sup>1</sup>		
	TRIM PACKER					OMEGQPR10 <sup>1</sup>		
		GEARBOX PACKER KIT			1	GQGK01 <sup>3</sup>		

### OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
GQ Y60 CAB CHASSIS COIL SPRING MODELS	REAR	CONSTANT 440LBS TO GVW	SPRING	2"	1	2GQ02J	
		NITROCHARGER SPORT	SHOCK		2	60015	
		NITROCHARGER	SHOCK		2	*N29/N22F	
	REQ'D FOR INSTALLATION	TRIM PACKER					OMEGQPR05 <sup>1</sup>
		TRIM PACKER					OMEGQPR10 <sup>1</sup>
		GEARBOX PACKER KIT				1	GQGK01 <sup>3</sup>

<sup>1</sup> COIL TRIM PACKERS MAY BE REQUIRED TO TRIM VEHICLE TO A MAXIMUM OF .59" PER COIL. PACKERS MUST BE INSTALLED ON THE TOP ON REAR COILS AND TO THE BOTTOM ON FRONT COILS. PART No. OMEGQPF10 & OMEGQPR10 = .39". PART No. OMEGQPR10 & OMEGQPR05 = .20"

<sup>2</sup> OMECA77B CASTER KIT WILL INCREASE CASTER ANGLE BY 2°. CASTER ANGLE WILL BE AFFECTED WHEN RAISING VEHICLE. CHECK MANUFACTURER'S SPECIFICATIONS TO DETERMINE IF OMECA77B IS REQUIRED.

<sup>3</sup> GEARBOX PACKER KIT IS DESIGNED TO SPACE DOWN THE GEARBOX CROSS MEMBER FROM THE CHASSIS TO REDUCE TAIL SHAFT FLANGE ANGLE THEREBY REDUCING DRIVELINE VIBRATION.

### OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
PATROL GQ Y60 UTE & CAB CHASSIS LEAF SPRING MODELS	FRONT	LIGHT LOAD TO 110LBS	SPRING	1"	2	CS003F <sup>1</sup>	
			SHOCK		2	N28	
	REQ'D FOR INSTALLATION	SPRING BUSH				2	OMESB1
		GREASABLE SHACKLE				1	OMEGS2
		GREASABLE SHACKLE				1	OMEGP2
STEERING DAMPER				1	OMESD22		
PATROL GQ Y60 UTE & CAB CHASSIS LEAF SPRING MODELS	FRONT	HEAVY LOAD 110 TO 240LBS	SPRING	1"	2	CS004F <sup>1</sup>	
			SHOCK		2	N28	
	REQ'D FOR INSTALLATION	SPRING BUSH				2	OMESB1
		GREASABLE SHACKLE				1	OMEGS2
		GREASABLE SHACKLE				1	OMEGP2
STEERING DAMPER				1	OMESD22		
PATROL GQ Y60 UTE & CAB CHASSIS LEAF SPRING MODELS	REAR	MEDIUM LOAD TO GVW	SPRING	1.75"	2	CS016RA/B	
			SHOCK		2	N25	
	REQ'D FOR INSTALLATION	SPRING BUSH				2	OMESB64
		GREASABLE SHACKLE				1	OMEGS1
		GREASABLE SHACKLE				1	OMEGP2
		U BOLTS				4	OMEU58B
	ANTI INVERSION KIT				1	FK08 <sup>2</sup>	
	REAR	CONSTANT 880LBS TO GVW	SPRING	1.75"	2	CS016RA/B	
			SHOCK		2	N25	
	REQ'D FOR INSTALLATION	SPRING BUSH				2	OMESB64
GREASABLE SHACKLE					1	OMEGS1	
GREASABLE SHACKLE					1	OMEGP2	
U BOLTS					4	OMEU58B	
ANTI INVERSION KIT				1	FK08 <sup>2</sup>		

<sup>1</sup> CBS02 x 2 CENTER BOLT SPACERS REQUIRED FOR FRONT SPRING FITMENT.

<sup>2</sup> FK08 ANTI INVERSION KIT IS MANDATORY FITMENT IF GREASABLE SHACKLES ARE NOT FITTED.

## PATROL GQ

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES						
YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1988-98	FRONT	H233B	32 (1.26")	31	ALL	RD136
	REAR	H233B, REAR DISC BRAKES	33.3 (1.31")	33	ALL	RD135
		H233B, REAR DRUM BRAKES	33.3 (1.31")	33	ALL	RD135
		H260, LEAF SPRUNG CAB CHASSIS & UTILITY	38.4 (1.51")	37	ALL	RD70

<sup>1</sup> ONLY SUITABLE FOR DIFFERENTIALS WITH 12MM RING GEAR BOLTS.

<sup>2</sup> REFER TO DEALER OR CHECK SPLINE COUNT TO DETERMINE AXLE TYPE.

ARB ROOF RACKS		
YEAR	DESCRIPTION	PART NO.
GQ LWB AND SWB <sup>1</sup>	87X49" STEEL RACK WITH MESH FLOOR	3800010M
	87X49" STEEL RACK WITHOUT MESH FLOOR	3800010
	87X49" ALLOY RACK WITH MESH FLOOR	4900010M
	87X49" STEEL TOURING RACK FOR ROOF TOP TENT	3800200
	FITTING KIT FOR 87X49" RACKS (ALLOY & STEEL)	3700050
	73X49" STEEL WITH MESH FLOOR	3800020M
	73X49" STEEL WITHOUT MESH FLOOR	3800020
	FITTING KIT FOR 73X49" RACKS	3700050
	43X49" STEEL RACK WITH MESH FLOOR	3800030M
	FITTING KIT FOR 43X49" RACKS	3700060
OPTIONAL	WIND DEFLECTOR FOR 49" WIDE ROOF RACK	3700310
	HI-LIFT JACK AND SHOVEL HOLDER FOR ARB ROOF RACK	K6202

<sup>1</sup>Use 43" x 49" RACK FOR SWB VEHICLES WITH STEEL ROOF