

LAND CRUISER 70/73/74 SERIES (PRE 2007 MODELS)

ARB DELUXE BULL BARS & WINCH BARS

YEAR	MODEL	FEATURES	WINCHES	PART NO.
ALL	WINCH BAR	TOW POINTS, RECESSED INDICATORS, BLACK	9.5XP, M12000, XD9000, M8274	3412130

IPF LIGHTING & ACCESSORIES

YEAR	RECOMMENDED LIGHTING
1985-07	800XSD, 900XS, 900HID, 868CS, 968CSG
	920HJKTJ - 7" ROUND H4 HEADLAMP CONVERSION KIT (H4 BULBS, NOT INCLUDED)
	820H - RECTANGULAR H4 HEADLAMP CONVERSION LENS (H4 BULBS NOT INCLUDED)

SAFARI SNORKEL

YEAR	RECOMMENDED SNORKEL	PART NO.
ALL	3B DIESEL, RIGHT SIDE MOUNT.	SS73HF

REFER TO WWW.SAFARI4x4.COM.AU FOR DETAILS.

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
ALL GAS & DIESEL, SWB & MWB 70 SERIES MODELS	FRONT	ALL MODELS - LIGHT LOAD TO 110LBS	SPRING	2.0"	2	CS006F	
		NITROCHARGER SPORT	SHOCK		2	60009	
	REQ'D FOR INSTALLATION	SPRING BUSHING				2	OMESB1
		GREASABLE SHACKLE				1	OMEGS2
		GREASABLE PIN KIT				1	OMEGP1
		TRIM PACKER					TP01
		STEERING DAMPER				1	OMESD24
		FRONT	HEAVY LOAD 110 TO 240LBS	SPRING	2.0"	2	CS006F
		NITROCHARGER SPORT	SHOCK			2	60009
	REQ'D FOR INSTALLATION	SPRING BUSHING				2	OMESB1
		U BOLT				4	OMEU51
		GREASABLE SHACKLE				1	OMEGS2
		GREASABLE PIN KIT				1	OMEGP1
		TRIM PACKER					TP01
STEERING DAMPER					1	OMESD24	
ALL GAS & DIESEL, SWB & MWB 70 SERIES MODELS	REAR	MEDIUM LOAD TO GVW	SPRING	2.75"	2	CS017RA/B	
		NITROCHARGER SPORT	SHOCK		2	60062	
		NITROCHARGER	SHOCK		2	N85	
	REQ'D FOR INSTALLATION	SPRING BUSHING				2	OMESB1
		U BOLT				4	OMEU59A
		GREASABLE SHACKLE				1	OMEGS2
		GREASABLE PIN KIT				1	GSP01
	REAR	CONSTANT 440LB LOAD TO GVW	SPRING	2.75"		2	CS004RA/B ²
		NITROCHARGER SPORT	SHOCK			2	60062
		NITROCHARGER	SHOCK			2	N85
REQ'D FOR INSTALLATION		ANTI INVERSION KIT**			1	FK08	

CONTINUED ON NEXT PAGE

LAND CRUISER 70/73/74 SERIES (PRE 2007 MODELS)

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
ALL GAS & DIESEL, SWB & MWB 70 SERIES MODELS	INSTALLATION	SPRING BUSHING			2	OMESB1
		U BOLT			4	OMEU59A
		GREASABLE SHACKLE			1	OMEGS2
		GREASABLE PIN KIT			1	GSP01
		ANTI INVERSION KIT**			1	FK08

¹ CS006FM IS A MODIFIED CS006F SPRING (4TH LEAF FROM TOP OF SPRING STACK REMOVED.) USE WHERE BUMP STOP HEIGHTS EXCEED 3.93".

² IF BUMP STOP MEASUREMENT EXCEEDS 59-63" REMOVE THIRD LEAF FROM TOP OF SPRING STACK TO PREVENT SHOCK ABSORBER FROM TOPPING OUT.

** ANTI INVERSION KIT FK08 IS REQUIRED FOR INSTALLATION IF GREASABLE SHACKLES ARE NOT INSTALLED.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
TO 1989	FRONT	12 BOLT	33 (1.31")	30	ALL	RD142
	REAR	12 BOLT, SEMI FLOAT	33 (1.31")	30	ALL	RD153