

## LAND CRUISER 80 SERIES/LEXUS 450

ARB DELUXE BULL BARS & WINCH BARS				
YEAR	MODEL	FEATURES	WINCHES	PART NO.
1990-97	WINCH BAR: 80 SERIES	RECESSED INDICATORS, TOW POINTS, BLACK	M12000, XD9000 <sup>2</sup> , M8000 <sup>2</sup>	3411050
1990-97	BULL BAR: 80 SERIES	RECESSED INDICATORS, TOW POINTS, BLACK	N/A	3211050
1996-97	WINCH BAR: LX450	RECESSED INDICATORS, TOW POINTS, BLACK	M12000, XD9000, M8000 <sup>2</sup>	3411050

<sup>2</sup> FITMENT OF WARN XD9000 & M8000 WINCH REQUIRES SPECIAL SPACER KIT - ARB PART NO. 3500050.

IPF LIGHTING & ACCESSORIES		
YEAR	MODEL	RECOMMENDED LIGHTING
1990-97	80 SERIES	800XSD, 868CS, 968CSG
	LX450	800XSD, 868CS, 968CS

ARB SLIDERS/SIDE RAILS/STEPS			
YEAR			PART NO.
1990-97	GXL & VX	ONE-PIECE SIDE PROTECTION RAILS AND STEPS TO SUIT MODELS WITH FENDER FLARES (REQUIRES ARB BUMPER FOR MOUNTING), BLACK	4411010 <sup>1</sup>
1990-97	STD, DX, RV & ADVANTAGE	ONE-PIECE SIDE PROTECTION RAILS AND STEPS TO SUIT MODELS WITHOUT FENDER FLARES (REQUIRES ARB BUMPER FOR MOUNTING), BLACK	4411030 <sup>1</sup>

<sup>1</sup> SIDE RAILS MAY REQUIRE CUSTOM BRACKETS ON PASSENGER SIDE FOR CATALYTIC CONVERTER CLEARANCE ON NORTH AMERICAN MODELS.

ARB MODULAR REAR PROTECTION BUMPERS WITH OPTIONAL SWING-OUT TIRE CARRIERS &/OR JERRY CAN HOLDERS			
YEAR	MODEL	DESCRIPTION	PART NO.
1990-97	LC80 & LX450	DELUXE REAR BAR, BLACK	5611210 <sup>1</sup>
		LHS BLANK COVER PANEL, BLACK	5700231 <sup>2</sup>
		RHS BLANK COVER PANEL, BLACK	5700232 <sup>2</sup>
		LHS TIRE CARRIER, BLACK	5711211 <sup>2</sup>
		RHS TIRE CARRIER, BLACK	5711212 <sup>2</sup>
		LHS JERRY CAN HOLDER, BLACK	5711221 <sup>2</sup>
		RHS JERRY CAN HOLDER, BLACK	5711222 <sup>2</sup>
	OPTIONAL	ANTENNA MOUNT LHS	5711031
		ANTENNA MOUNT RHS	5711032
		LHS CAMP LIGHT	5711041
		RHS CAMP LIGHT	5711042
		HILIFT MOUNT FOR WHEEL CARRIER ONLY	5700060
		REVERSING LIGHT KIT	5700070

<sup>1</sup> A LEFT OR RIGHT HAND SIDE COVER PANEL MUST BE USED FOR INSTALLATION IF TIRE CARRIER OR JERRY CAN HOLDER IS NOT PURCHASED

<sup>2</sup> CUSTOMER CAN USE A COMBINATION OF BLANKS, TIRE CARRIERS, OR JERRY CAN HOLDERS FOR A COMPLETE INSTALLATION

**A MINIMUM OF 3 SEPARATE PART NUMBERS WILL BE REQUIRED FOR THIS BAR TO MOUNT TO THE VEHICLE.**

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES						
YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1990-97	FRONT	10 BOLT, FULL FLOATING	33 (1.31")	30	ALL	RD132
1990-92 <sup>2</sup>	REAR	12 BOLT, SEMI FLOATING	33 (1.31")	30	ALL	RD153 <sup>1</sup>
1993 ON		12 BOLT, FULL FLOATING	33 (1.31")	30	ALL	RD142

<sup>1</sup> MUST USE LATE MODEL 50.00MM (1.969") ID BEARINGS WITH THIS LOCKER FOR THIS SPECIFIC APPLICATION (ARB PART NO. 160116)

<sup>2</sup> ONLY VEHICLES MADE IN NORTH AMERICA.

<sup>3</sup> RD132 SUPERCEDES RD23 MARCH 2007

### SAFARI SNORKEL

YEAR	RECOMMENDED SNORKEL	PART NO.
1990-97	ALL MODELS	SS81HF

REFER TO WWW.SAFARI4x4.COM.AU FOR DETAILS.

### OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
80 SERIES & LX450	FRONT	STOCK/LIGHT LOAD (0-110LBS)	SPRING	2.0"	1	2851	
		NITROCHARGER SPORT	SHOCK		2	60018	
		NITROCHARGER	SHOCK		2	*N73/N70	
		HEAVY LOAD (110-250LBS)	SPRING	2.0"	1	2850	
		NITROCHARGER SPORT			2	60018	
		NITROCHARGER	SHOCK		2	N73	
		LOW HEIGHT HEAVY LOAD (110-250LBS)	SPRING	.25"	1	2861	
		NITROCHARGER SPORT			2	60018	
		NITROCHARGER	SHOCK		2	N73	
		REAR	MEDIUM LOAD (0LBS TO GVW)	SPRING	2.0"	1	2860
			NITROCHARGER SPORT			2	60020
			NITROCHARGER	SHOCK		2	*N74E/N71E
	CONSTANT LOAD (440LBS TO GVW)		SPRING	2.0"	1	2863	
	NITROCHARGER SPORT				2	60020	
	NITROCHARGER		SHOCK		2	N74E	
	HEAVY CONSTANT (880LBS TO GVW)		SPRING	1.50"	1	2864	
	NITROCHARGER SPORT				2	60020	
	NITROCHARGER		SHOCK		2	N74E	
	LOW HEIGHT MEDIUM LOAD (0LBS TO GVW)		SPRING	.75"	1	2862	
	NITROCHARGER SPORT				2	60020	
	NITROCHARGER		SHOCK		2	*N74E/N71E	
	REQ'D FOR INSTALLATION	CASTER KIT			1	OMECA77B <sup>1</sup>	
		STEERING DAMPER			1	OMESD24	
	OPTIONAL	REAR SHOCK STONE GUARD			1	OME661 <sup>2</sup>	
FRONT TRIM SPACER 5MM					OME80PF05 <sup>3</sup>		
FRONT TRIM SPACER 10MM					OME80PF10 <sup>3</sup>		
REAR TRIM SPACER 5MM					OME80PR05 <sup>3</sup>		
REAR TRIM SPACER 10MM					OME80PR10 <sup>3</sup>		
FRONT LTR SHOCKS				2	LTR01F <sup>4</sup>		
REAR LTR SHOCKS				2	LTR01RR/L <sup>4</sup>		

<sup>1</sup> OMECA77B CASTER KIT WILL INCREASE CASTER BY 2 DEGREES. CASTER ANGLE WILL BE AFFECTED WHEN RAISING THE VEHICLE. CHECK MANUFACTURER'S SPECIFICATIONS TO DETERMINE IF OMECA77B IS REQUIRED.

<sup>2</sup> OME661 LOWER SHOCK MOUNT STONE GUARD IS RECOMMENDED FITMENT TO REAR SHOCKS TO PROTECT AGAINST SEVERE STONE PEPPERING ENCOUNTERED ON LOOSE ROAD SURFACES.

<sup>3</sup> TRIM SPACERS MAY BE REQUIRED TO TRIM THE VEHICLE TO A MAXIMUM OF 15MM PER COIL. PACKERS MUST BE INSTALLED ON THE TOP END OF COIL SPRING.

<sup>4</sup> LTR REMOTE RESERVOIR SHOCK ABSORBERS ARE FOR COMPETITION USE AND REQUIRE REGULAR MAINTENANCE.

<sup>5</sup> 2850J/863J COILS AND EXTENDED LENGTH SHOCKS SHOULD BE INSTALLED TOGETHER, ALTHOUGH THEY DO NOT COMPRISE A KIT. FITMENT OF EXTENDED LENGTH SHOCKS REQUIRES MANDATORY INSTALLATION OF .75" (20MM) FRONT AND 1.25" (30MM) REAR BUMP FROM BOTTOMING OUT UNDER FULL COMPRESSION. THESE BUMP STOP SPACERS ARE NOT AVAILABLE FROM OME AND WILL NEED TO BE SOURCED BY THE INSTALLER.

\* FIRMER SHOCKS

## LAND CRUISER 80 SERIES/LEXUS 450

### OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
80 SERIES & LX450	ALSO AVAIL-ABLE	FRONT EXTENDED HEIGHT COIL SPRINGS	SPRING	3"	1	2850J <sup>5</sup>
		FRONT EXTENDED LENGTH SPORT SHOCK	SHOCK		2	60070L <sup>5</sup>
		REAR EXTENDED HEIGHT COIL SPRINGS	SPRING	3"	1	2863J <sup>5</sup>
		REAR EXTENDED LENGTH SPORT SHOCK	SHOCK		2	60071L <sup>5</sup>

<sup>1</sup> OMECA77B CASTER KIT WILL INCREASE CASTER BY 2 DEGREES. CASTER ANGLE WILL BE AFFECTED WHEN RAISING THE VEHICLE. CHECK MANUFACTURER'S SPECIFICATIONS TO DETERMINE IF OMECA77B IS REQUIRED.

<sup>2</sup> OME661 LOWER SHOCK MOUNT STONE GUARD IS RECOMMENDED FITMENT TO REAR SHOCKS TO PROTECT AGAINST SEVERE STONE PEPPERING ENCOUNTERED ON LOOSE ROAD SURFACES.

<sup>3</sup> TRIM SPACERS MAY BE REQUIRED TO TRIM THE VEHICLE TO A MAXIMUM OF 15MM PER COIL. PACKERS MUST BE INSTALLED ON THE TOP END OF COIL SPRING.

<sup>4</sup> LTR REMOTE RESERVOIR SHOCK ABSORBERS ARE FOR COMPETITION USE AND REQUIRE REGULAR MAINTENANCE.

<sup>5</sup> 2850J/863J COILS AND EXTENDED LENGTH SHOCKS SHOULD BE INSTALLED TOGETHER, ALTHOUGH THEY DO NOT COMPRISE A KIT. FITMENT OF EXTENDED LENGTH SHOCKS REQUIRES MANDATORY INSTALLATION OF .75" (20MM) FRONT AND 1.25" (30MM) REAR BUMP FROM BOTTOMING OUT UNDER FULL COMPRESSION. THESE BUMP STOP SPACERS ARE NOT AVAILABLE FROM OME AND WILL NEED TO BE SOURCED BY THE INSTALLER.

\* FIRMER SHOCKS

### ARB ROOF RACKS

YEAR	DESCRIPTION	PART NO.
80 SERIES & LX450	87X49" STEEL RACK WITH MESH FLOOR	3800010M
	87X49" STEEL RACK WITHOUT MESH FLOOR	3800010
	87X49" ALLOY RACK WITH MESH FLOOR	4900010M
	87X49" STEEL TOURING RACK FOR ROOF TOP TENT	3800200
	FITTING KIT FOR 87X49" RACKS	3700050
	73X49" STEEL RACK WITH MESH FLOOR	3800020M
	73X49" STEEL RACK WITHOUT MESH FLOOR	3800020
	FITTING KIT FOR 73X49" RACKS	3700050
	43X49" STEEL RACK WITH MESH FLOOR	3800030M
	FITTING KIT FOR 43X49" RACKS	3700060
OPTIONAL	WIND DEFLECTOR FOR 49" WIDE ROOF RACK	3700310
	HI-LIFT JACK AND SHOVEL HOLDER FOR ARB ROOF RACK	K6202
	DOUBLE JERRY CAN HOLDER. (WILL NOT FIT PLASTIC FUEL CANS)	3500390

### THULE ROOF RACK SYSTEM TO SUIT ARB ROOF TOP TENT

YEAR	MODEL	DESCRIPTION	PART NO.
1995-97	LC80	THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT	T45058

<sup>1</sup> REQUIRES OE RACKS TO COMPLETE INSTALLATION