

TUNDRA

ARB DELUXE BULL BARS & WINCH BARS				
YEAR	MODEL	FEATURES	WINCHES	PART NO.
1999-05	SAHARA BAR	AIRBAG APPROVED, RECESSED FOG LAMPS ¹ , URETHANE BUFFERS, TOW POINTS, SPLIT PAN	M15000, M12000	3915020 ²
2007-12	WINCH BAR	AIRBAG APPROVED, RECESSED FOG LAMPS ⁸ , TOW POINTS, SPLIT PAN	M16.5TI, M15000, M12000 ¹⁰	3415010 ^{3,9}
2007-12	SAHARA BAR	OPTIONAL ALLOY CENTER TUBE, AIRBAG APPROVED, RECESSED FOG LAMPS ⁷ , TOW POINTS, SPLIT PAN	M16.5TI, M15000, M12000 ¹⁰	3915030 ^{5,6,9}

- ¹ USES OPTIONAL IPF PART NUMBER 9381FCK
- ² CONTACT ARB FOR SPECIAL INSTRUCTIONS FOR FITTING BAR TO 2006 MODELS
- ³ FRONT SUSPENSION REQUIRED TO ACCOMMODATE THE ADDED WEIGHT OF THE ARB BUMPER
- ⁴ WILL WORK WITH OE FOG LAMPS, OR OPTIONAL ARB FOG LAMP KIT PART NO. 6821201. 3500440 REQUIRED WHEN FITTING 6821201 TO MODELS WITHOUT OE FOG LAMPS
- ⁵ OPTIONAL CHROME CENTER TUBE REQUIRES ADDITIONAL PART #'S 5100140 AND 5115030 TO COMPLETE INSTALLATION
- ⁶ IF THE OPTIONAL CHROME CENTER TUBE IS NOT BEING INSTALLED, ADDITIONAL PART # 5100150 IS REQUIRED TO COMPLETE INSTALLATION
- ⁷ OPTIONAL ARB FOG LAMP KIT PART NO. 6821201. 3500440 REQUIRED WHEN FITTING 6821201 TO MODELS WITHOUT OE FOG LAMPS
- ⁸ OE FOG LAMPS OR OPTIONAL IPF FOG LAMP KIT PART NUMBER 9381FCK
- ⁹ 2010+ MODELS WITH "MILLENNIUM" OR "LIMITED" GRILLS MAY NEED MODIFICATION. PLEASE CONTACT ARB FOR DETAILS (425) 264-1391
- ¹⁰ IF FITTING 12000LB WINCH, EXTRA LONG CABLE KIT 3512050 IS REQUIRED

IPF LIGHTING & ACCESSORIES		
YEAR	MODEL	RECOMMENDED LIGHTING
1999-06	3915020	800XSD, 900XSD, 900XSS, 900HIDD, 900HIDS, 968CSG, 868CS
2007-12	ALL	800XSD, 900XSD, 900XSS, 900HIDD, 900HIDS, 968CSG, 868CS

OLD MAN EMU SUSPENSION SYSTEMS							
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
2007-12	COMPLETE KITS	4.7L V8 STOCK/LIGHT LOAD (0-150LBS)	KIT	2.5"	1	OMETUN47LK	
		4.7L V8 HEAVY LOAD (200LBS+)	KIT	2.5"	1	OMETUN47HK	
		5.7L V8 STOCK/LIGHT LOAD (0-150LBS)	KIT	2.5"	1	OMETUN57LK	
		5.7L V8 HEAVY LOAD (200LBS+)	KIT	2.5"	1	OMETUN57HK	
	FRONT	STOCK/LIGHT LOAD (0-150LBS)	SPRING	2.50"	1	2612	
			STRUT		2	N192S	
		HEAVY LOAD 4.7 LITER ENGINE (200LBS+)	SPRING	2.50"	1	2614	
					2	N192S	
		HEAVY LOAD 5.7 LITER ENGINE (200LBS+)	SPRING	2.50"	1	2613	
			STRUT		2	N192S	
	REAR	MEDIUM LOAD (0LBS TO GVW)	SPRING	2.50"	2	CS055R ³	
			SHOCK		2	N193	
	REQ'D FOR INSTALLATION	FITTING KIT			1	FK32 ¹	
		U BOLTS			4	OMEU53B	
SPRING BUSH KITS					SEE NOTE ²		
OPTIONAL	EXTRA LEAF			2	D28XL		

- ** OME FRONT COILS CAN ONLY BE INSTALLED WITH OME NITROCHARGER STRUTS AND COIL SEATS.
- ¹ FK32 FITTING KIT IS A BRAKE LINE AND ABS WIRE BRACKET RELOCATION KIT AND IS A MANDATORY FITMENT.
 - ² NEW BONDED RUBBER BUSHES ARE SUPPLIED WITH THE LEAF SPRINGS
 - ³ TRD MODELS WITH REAR SWAYBARS WILL REQUIRE END LINK MODIFICATIONS TO RETAIN SWAYBAR OPERATION.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1999-04	FRONT	7.5" DIA. RG, 10 BOLT, IFS	28 (1.1")	27	ALL	RD90
2005-06	FRONT	8" DIA. RG, IFS, 53MM BEARING ID	33 (1.31")	30	3.91 & UP	RD111 ¹
		8" DIA. RG, IFS, 53MM BEARING ID	33 (1.31")	30	3.73 & DN	RD121 ¹
1999-06	REAR	8" DIA. RG, 12 BOLT	33 (1.31")	30	ALL	RD129
2007-12	FRONT	8" IFS, 58MM BEARING	35 (1.38")	34	ALL	RD141
2007-12	REAR	4.7 LITER ENGINE 9.5" DIA. RG	35 (1.37")	32	ALL	RD152
		5.7 LITER ENGINE 10.5" DIA RG		36	ALL	RD146

¹ AFTERMARKET GEARS MAY REQUIRE RD121 - CONFIRM WITH GEAR MANUFACTURER.