

LIBERTY KK

OLD MAN EMU SUSPENSION SYSTEMS						
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
2008-13	FRONT	GAS - STOCK/LIGHT LOAD (0-110LBS)	SPRING	1-1.5"	1	2926 ¹
		NITROCHARGER SPORT	STRUT		2	90009
		NITROCHARGER	STRUT		2	NS131 ²
	FRONT	GAS - MEDIUM LOAD (0-150LBS)	SPRING	1-1.5"	1	2927 ¹
		NITROCHARGER SPORT	STRUT		2	90009
		NITROCHARGER	STRUT		2	NS131 ²
	FRONT	DIESEL - STOCK/LIGHT LOAD	SPRING	1-1.5"	1	2927 ¹
		NITROCHARGER SPORT	STRUT		2	90009
		NITROCHARGER	STRUT		2	NS131 ²
	FRONT	DIESEL - MEDIUM LOAD (0-110LBS)	SPRING	1-1.5"	1	2790 ¹
		NITROCHARGER SPORT	STRUT		2	90009
		NITROCHARGER	STRUT		2	NS131 ²
2008-13	REAR	GAS/DIESEL - LIGHT LOAD	SPRING	1.5"	1	2730
		NITROCHARGER SPORT	SHOCK		2	60069
		NITROCHARGER	SHOCK		2	N132
	REAR	GAS/DIESEL - MEDIUM LOAD	SPRING	1.5"	1	2731
		NITROCHARGER SPORT	SHOCK		2	60069
		NITROCHARGER	SHOCK		2	N132

¹ DUE TO VARYING OE RIDE HEIGHTS, SOME KK MODELS MAY ONLY ACHIEVE A .75" LIFT.

² NO TOP MOUNTING BUSHINGS SUPPLIED, RE-USE OE BUSHINGS.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES						
YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
2008-13	FRONT	DANA 30 IFS	29.5 (1.16")	27	3.73 & UP	RD100
					3.54 & DN	RD101
2008-13	REAR	CHRYSLER 8.25" DIA. RG C-CLIP	30.7 (1.21")	29	ALL	RD93 ¹

¹ NEWER OEM DANA 35, 44 & CHRYSLER 8.25" RING GEARS MAY HAVE 3/8", 7/16", OR 1/2" RING GEAR BOLTS. AIR LOCKER FLANGE HOLES MUST BE DRILLED OR REAMED LARGE TO SUIT 7/16" OR 1/2" BOLTS.