

4RUNNER

ARB DELUXE BULL BARS & WINCH BARS

YEAR	MODEL	FEATURES	WINCHES	PART NO.
2014 ON	SUMMIT BAR INTEGRIT FINISH	SRS APPROVED, INDICATORS, RECESSED FOG LAMPS, LED INDICATORS, HI-LIFT JACK POINTS	M8000, XD9000, XP9.5, XDC9.5, ZEON 8 ^{4,6} , 10 ^{4,6} , ZEON PLATINUM	3421560K ^{3,4,5,6,7}
2010-13	WINCH BAR	AIRBAG APPROVED, INDICATORS, RECESSED FOG LAMPS ² , SATIN BLACK FINISH	9.5XP, HS9500, XD9000	3421520
2006-09	WINCH BAR INTEGRIT FINISH	AIRBAG APPROVED, INDICATORS, RECESSED FOG LAMPS ² , INTEGRIT BLACK FINISH	9.5XP, HS9500, XD9000,	3421540
2003-05	WINCH BAR	AIRBAG APPROVED, INDICATORS, RECESSED FOG LAMPS ² , INTEGRIT BLACK FINISH	9.5XP, HS9500, XD9000,	3421530
1986-95	WINCH BAR	RECESSED INDICATORS, TOW POINTS, BLACK	XD9000, M8000	3414070 ¹

¹ FITMENT OF BAR TO 4RUNNER MODELS MAY REQUIRE MODIFICATIONS - CONTACT ARB FOR DETAILS.

² OPTIONAL ON THIS MODEL - ARB FOG LAMP KIT PART NO. 6821201. ARB FOG LAMP HARNESS PART NO. 3500440 REQUIRED WHEN FITTING 6821201 TO MODELS WITHOUT OE FOG LAMPS

³ 3421550K INCLUDES SUMMIT COMBO BAR, ARB RECESSED FOG LAMPS AND FOG LAMP HARNESS

⁴ OPTIONAL HAWSE FAIRLEAD SPACER KIT PART NO 3500600 REQUIRED WHEN FITTING A HAWSE FAIRLEAD

⁵ OPTIONAL ROLLER FAIRLEAD COVER 3500850 AVAILABLE

⁶ WARN PART NO W89965 REQUIRED WHEN FITTING WARN ZEON AND ZEON PLATINUM WINCH

⁷ DESIGNED FOR SR5, TRAIL AND TRD MODELS. **WILL NOT FIT LIMITED MODELS.**

SAFARI SNORKEL

YEAR	RECOMMENDED SNORKEL	PART NO.
2010-17	SAFARI ARMAX SNORKEL - 4RUNNER 5TH GENERATION - ALL ENGINES	SS450HP
1989-94	3.0L, V6 SNORKEL - NEEDS MODIFICATIONS	SS130HF
1984-88	2.0L/2.2L SNORKEL - NEEDS MODIFICATIONS	SS65HF

UNDER VEHICLE SKID PLATES

YEAR	DESCRIPTION	PART NO.
2010-18	2010-16 TOYOTA 4RUNNER WITH KINETIC (KDSS) SYSTEM	5421110
2010-18	2010-16 TOYOTA 4RUNNER WITHOUT KINETIC (KDSS) SYSTEM	5421100

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
2003-ON	FRONT	8" DIA. RG, IFS, 53MM BEARING ID	33 (1.31")	30	3.91 & UP	RD111 ³
2003-ON		8" DIA. RG, IFS, 53MM BEARING ID	33 (1.31")	30	3.73 & DN	RD121 ³
TO 2002		8" DIA. RG, 10 BOLT, LIVE AXLE	33 (1.31")	30	ALL	RD132
TO 2002	REAR	7.5 DIA. RG 10 BOLT, IFS	28 (1.1")	27	ALL	RD90
1984-88		4 CYLINDER, 45MM CARRIER BEARING	33 (1.31")	30	ALL	RD132 ¹
1988-09		V6, 4WD, 50MM CARRIER BEARING	33 (1.31")	30	ALL	RD132 ²
1988-09		V6,2WD, 45MM CARRIER BEARING	33 (1.31")	30	ALL	RD132 ^{1,2}
2010-ON		8.25" DIA RG, 12-BOLT (SHIMMED)	33 (1.31")	30	ALL	RD193 ²

¹ LATE MODEL 50.00MM (1.969") ID BEARINGS MUST BE USED WITH THIS SPECIFIC APPLICATION. (ARB PART NO. 160116)

² SUITS OPEN DIFFERENTIAL CARRIERS ONLY. WILL NOT WORK WITH FACTORY LOCKER OPTIONED 3RD MEMBERS

³ AFTERMARKET GEARS MAY REQUIRE RD121 - CHECK WITH GEAR MANUFACTURER

OLD MAN EMU SUSPENSION SYSTEMS						
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
2010 CURRENT	COMPLETE KITS	MEDIUM LOAD BP-51 KIT - NON KDSS	KIT	3"	1	OME4RNR10MKBP51
		HEAVY LOAD BP-51 KIT - NON KDSS	KIT	3"	1	OME4RNR10HKBP51
		MEDIUM LOAD BP-51 KIT - WITH KDSS	KIT	3"	1	OME4RNR10MKBP51KD
		HEAVY LOAD BP-51 KIT - WITH KDSS	KIT	3"	1	OME4RNR10HKBP51KD

OLD MAN EMU SUSPENSION SYSTEMS							
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
2010-CURRENT	FRONT	LIGHT LOAD - STOCK WEIGHT - NO BAR OR WINCH	SPRING	3"	1	2884 ⁴	
		NITROCHARGER SPORT	STRUT		2	90010 ⁵	
		MEDIUM LOAD - WITH BAR OR WINCH ONLY (70-180LBS)	SPRING	3"	1	2885 ⁴	
		NITROCHARGER SPORT	STRUT		2	90010 ⁵	
		HEAVY LOAD - WITH BAR AND WINCH (230LBS+)	SPRING	3"	1	2887 ⁴	
		NITROCHARGER SPORT	STRUT		2	90010 ⁵	
	OPTIONAL		FRONT TRIM SPACER 5MM				OME95PF5 ¹
	REAR	MEDIUM LOAD	SPRING	3"	1	2889	
		NITROCHARGER SPORT	SHOCK		2	60080 ⁶	
		HEAVY LOAD (440LBS CONSTANT LOAD)	SPRING	3"	1	2898	
		NITROCHARGER SPORT	SHOCK		2	60081/60080 ⁶	
HEAVY LOAD (880LBS CONSTANT LOAD)		SPRING	3"	1	2899		
NITROCHARGER SPORT		SHOCK		2	60081 ³		
OPTIONAL		OPTIONAL REAR SPORT SHOCK GUARD				OME661	
OPTIONAL BP-51 INTERNAL BYPASS	VEHICLES WITHOUT KDSS SYSTEM	BP-51 COIL OVER - FRONT RHS	COIL OVER	3"	1	BP5190002R ¹	
		BP-51 COIL OVER - FRONT - LHS	COIL OVER	3"	1	BP5190002L ¹	
		BP-51 SHOCK - REAR	SHOCK		2	BP5160025 ²	
		VEHICLE MOUNT KIT FRONT	MOUNT KIT		1	VM80010028 ¹	
		VEHICLE MOUNT KIT REAR	MOUNT KIT		1	VM80010010 ²	
	VEHICLES WITH KDSS SYSTEM	BP-51 COIL OVER - FRONT - RHS	COIL OVER	3"	1	BP5190002R ³	
		BP-51 COIL OVER - FRONT - LHS	COIL OVER	3"	1	BP5190004L ³	
		BP-51 SHOCK - REAR	SHOCK		2	BP5160025 ²	
		VEHICLE MOUNT KIT FRONT	MOUNT KIT		1	VM80010009 ³	
		VEHICLE MOUNT KIT REAR	MOUNT KIT		1	VM80010010 ²	

¹ VEHICLE MOUNT KIT PART NUMBER **VM80010028** REQUIRED WHEN FITTING BP-51 PART NUMBER **BP5190002R** AND **BP5190002L**

² VEHICLE MOUNT KIT PART NUMBER **VM80010010** REQUIRED WHEN FITTING BP-51 PART NUMBER **BP5160025**

³ VEHICLE MOUNT KIT PART NUMBER **VM80010009** REQUIRED WHEN FITTING BP-51 PART NUMBER **BP519002R** AND **BP5190004L**

⁴ VEHICLES WITH KDSS MUST HAVE 1 x OME95PF5 SPACER INSTALLED ON THE DRIVER'S SIDE TO MAINTAIN CORRECT TRIM.

⁵ NO TOP MOUNTING BUSHINGS ARE SUPPLIED. RE-USE OE BUSHINGS.

⁶ OME661 LOWER SHOCK MOUNT STONE GUARD IS RECOMMENDED FOR REAR SHOCKS TO PROTECT AGAINST STONE CHIP DAMAGE.

4RUNNER

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.		
2003-09 MODELS	FRONT	LIGHT LOAD - STOCK WEIGHT - NO BAR OR WINCH	SPRING	1.0"	1	2884 ¹		
		NITROCHARGER SPORT	STRUT		2	*90000 / 90021		
		NITROCHARGER	STRUT		2	N140S		
		MEDIUM LOAD - WITH BAR OR WINCH ONLY (70-180LBS)	SPRING	2.0"	1	2885 ¹		
		NITROCHARGER SPORT	STRUT		2	90000		
		NITROCHARGER	STRUT		2	N140S		
		HEAVY LOAD - WITH BAR AND WINCH (230LBS+)	SPRING	2.5"	1	2886 ¹		
		NITROCHARGER SPORT	STRUT		2	90000		
	REAR	REAR	MEDIUM LOAD	SPRING	2.0"	1	2895	
			NITROCHARGER SPORT	SHOCK		2	60004	
			HEAVY LOAD (330LBS TO GVW)	SPRING	2.0"	1	2896	
			NITROCHARGER SPORT	SHOCK		2	*60005/60004	
			HEAVY CONSTANT LOAD (660LBS TO GVW)	SPRING	2.0"	1	2897	
			NITROCHARGER SPORT	SHOCK		2	60005	
			OPTIONAL	FRONT TRIM SPACER 5MM				OME95PF5

¹ IMPORTANT: OME FRONT COILS CAN ONLY BE INSTALLED WITH OME NITROCHARGER STRUT AND COIL SEATS.

* FIRMER VALVE SHOCK

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
1996-02 MOD- ELS	FRONT	STOCK/LIGHT LOAD (0-110LBS)	SPRING	1.25"	1	2880	
		NITROCHARGER SPORT	SHOCK		2	90004	
		HEAVY LOAD (110-240LBS)	SPRING	1.25"	1	2881	
		NITROCHARGER SPORT	SHOCK		2	90004	
	REAR	REAR	MEDIUM LOAD	SPRING	2.0"	1	2890
			NITROCHARGER SPORT - SOFT VALVING	SHOCK		2	60073
			NITROCHARGER SPORT - FIRM VALVING	SHOCK		2	60028
			HEAVY LOAD (330LBS TO GVW)	SPRING	2.0"	1	2906
			NITROCHARGER SPORT	SHOCK		2	60027
			HEAVY CONSTANT LOAD (660LBS TO GVW)	SPRING	2.0"	1	2891
			NITROCHARGER SPORT	SHOCK		2	60027
	OPTIONAL	OPTIONAL	FRONT TRIM PACKER 5MM				OME95PF5
			REAR TRIM PACKER 5MM				OME80PF05
REAR TRIM PACKER 10MM						OME80PF10	

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
IFS REAR LEAF SPRING PRE 1990 & IFS REAR COILS SPRING 1990-95	FRONT	STOCK/LIGHT LOAD	TORSION	N/A	1	303003 ¹
		NITROCHARGER SPORT	SHOCK		2	60072
IFS REAR COIL SPRING MOD- ELS 1990-95	REAR	MEDIUM LOAD (0LBS TO GVW)	SPRING	1.5"	1	2900
		NITROCHARGER SPORT	SHOCK		2	60073
		HEAVY LOAD (330LBS CONSTANT LOAD)	SPRING	1.5"	1	2901
		NITROCHARGER SPORT	SHOCK		2	60073
IFS REAR LEAF SPRING MODELS PRE 1990	REAR	MEDIUM LOAD (0LBS TO GVW)	SPRING	2.0"	2	CS009R ³
		NITROCHARGER SPORT	SHOCK		2	*60062/60065
		HEAVY CONSTANT (440LBS TO GVW)	SPRING	2.25"	2	CS010R ³
		NITROCHARGER SPORT	SHOCK		2	60065
REQ'D FOR INSTALLATION (LEAF SPRING- MODELS ONLY)		REAR LEAF SPRING BUSHING KIT			2	OMESB6
		U BOLTS			4	OMEU53 ²
		STEERING DAMPER			1	OMESD33
		BUSHING SLEEVE			2	181469
	OPTIONAL	GREASABLE SHACKLE KIT			1	OMEGS3
		REAR EXTRA LEAF				D5XL

¹ ADJUST FRONT TORSION BAR FOR ADDITIONAL HEIGHT AFTER INSTALLING REAR SPRINGS. SET RIDE HEIGHT TO 1/3 UPPER BUMP STOP CLEARANCE AND 2/3 LOWER BUMP STOP CLEARANCE.

² INSTALL OE CASTER WEDGES FROM OE SPRING PACK ONTO OME SPRINGS. ENSURE WEDGES ARE FITTED AS PER ORIGINAL POSITION.

³ COMPARE ORIGINAL SPRING PACK HEIGHT TO OME SPRING PACK TO DETERMINE WHETHER OMEU53 OR OMEU53B U BOLTS ARE REQUIRED.

⁴ EXTRA LEAF CAN BE FITTED FOR HEAVIER CONSTANT LOAD CARRYING ABILITY.

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
ALL LEAF SPRINGS 1984-85	FRONT	STOCK/LIGHT LOAD (0-110LBS)	SPRING	2.0"	2	CS008FA/B
		NITROCHARGER SPORT	SHOCK	2.0"	2	60061
		HEAVY LOAD (110-240LBS)	SPRING	2.0"	2	CS009FA/B
		NITROCHARGER SPORT	SHOCK	2.0"	2	60061
	REAR	MEDIUM LOAD (0LBS TO GVW)	SPRING	2.0"	2	CS009R ⁷
		NITROCHARGER SPORT - POST '84	SHOCK	2.0"	2	*60065/60062
		NITROCHARGER SPORT - PRE '84	SHOCK	2.0"	2	*60064/60032
		HEAVY CONSTANT (550LBS TO GVW)	SPRING	2.25"	2	CS010R ⁷
		NITROCHARGER SPORT - POST '84	SHOCK	2.25"	2	60065
		NITROCHARGER SPORT - PRE '84	SHOCK	2.25"	2	60064

¹ A/A SPRING FITMENT MAY BE NEEDED ON SOME VEHICLES FOR TRIMMING PURPOSES.

² CAN BE USED ON FRONT APPLICATION ONLY

³ SHOCK SELECTION 60064/60032 FOR MEDIUM AND 60064 FOR HEAVY APPLICATIONS APPLIES TO VEHICLES UP TO 1984 DUE TO A 16MM EYE AND SHORTER OPEN AND CLOSED LENGTHS. POST 1984 VEHICLES WITH 19MM EYE USE 60065/60062 FOR MEDIUM APPLICATIONS AND 60065 FOR HEAVY APPLICATIONS.

⁴ OMEU52 IS REQUIRED WHEN FITTING CS009FA/B OR CS008FA/B SPRINGS BECAUSE ORIGINAL U BOLT WILL FOUL DRAG LINK ON FULL DROOP. REFER TO OME FITTING MANUAL.

⁵ PICK UP MODELS MAY REQUIRE AN FK03 (SADDLE CORRECTION PLATES) IF THE SPRING SEATS ARE DISTORTED. FK10 MUST BE FITTED TO ALL MODELS USED CONTINUALLY OFF ROAD. REFER TO OME FITTING MANUAL.

⁶ EXTRA LEAF CAN BE FITTED FOR HEAVIER CONSTANT LOAD CARRYING ABILITY.

⁷ A TRIM SPACER MAY BE REQUIRED TO TRIM VEHICLE. ONLY TO BE USED ON REAR SPRINGS. IMPORTANT: INSTALL LEAF SPRINGS WITH MILITARY WRAP AT THE FIXED END.

4RUNNER

OLD MAN EMU SUSPENSION SYSTEMS

MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
ALL LEAF SPRINGS 1984-85	REQ'D FOR INSTALLATION	FRONT LEAF SPRING BUSHING KIT			2	OMESB5	
		REAR LEAF SPRING BUSHING KIT			2	OMESB6	
		FRONT U-BOLTS			1	OMEU52 ⁴	
		REAR U-BOLTS			4	OMEU53	
		BUSHING SLEEVE			2	181469	
	OPTIONAL	STEERING DAMPER				1	OMESD21
		FRONT GREASEABLE SHACKLE KIT				1	OMEGS4
		REAR GREASEABLE SHACKLE KIT				1	OMEGS3
		GREASEABLE PIN KIT				1	OMEGP3 ²
		REAR ANTI INVERSION KIT (PRE '84)				1	FK09 ⁵
		REAR ANTI INVERSION KIT (POST '84)				1	FK13 ⁵
		FRONT FITTING KIT				1	FK03/FK10 ⁵
		FRONT EXTRA LEAF					D17XL ⁶
		REAR EXTRA LEAF					D5XL ⁶
REAR TRIM SPACER					TP04 ⁷		

¹ A/A SPRING FITMENT MAY BE NEEDED ON SOME VEHICLES FOR TRIMMING PURPOSES.

² CAN BE USED ON FRONT APPLICATION ONLY

³ SHOCK SELECTION 60064/60032 FOR MEDIUM AND 60064 FOR HEAVY APPLICATIONS APPLIES TO VEHICLES UP TO 1984 DUE TO A 16MM EYE AND SHORTER OPEN AND CLOSED LENGTHS. POST 1984 VEHICLES WITH 19MM EYE USE 60065/60062 FOR MEDIUM APPLICATIONS AND 60065 FOR HEAVY APPLICATIONS.

⁴ OMEU52 IS REQUIRED WHEN FITTING CS009FA/B OR CS008FA/B SPRINGS BECAUSE ORIGINAL U BOLT WILL FOUL DRAG LINK ON FULL DROOP. REFER TO OME FITTING MANUAL.

⁵ PICK UP MODELS MAY REQUIRE AN FK03 (SADDLE CORRECTION PLATES) IF THE SPRING SEATS ARE DISTORTED. FK10 MUST BE FITTED TO ALL MODELS USED CONTINUALLY OFF ROAD. REFER TO OME FITTING MANUAL.

⁶ EXTRA LEAF CAN BE FITTED FOR HEAVIER CONSTANT LOAD CARRYING ABILITY.

⁷ A TRIM SPACER MAY BE REQUIRED TO TRIM VEHICLE. ONLY TO BE USED ON REAR SPRINGS. IMPORTANT: INSTALL LEAF SPRINGS WITH MILITARY WRAP AT THE FIXED END.

ARB ROOF RACKS

YEAR	DESCRIPTION	PART NO.
2003-CURRENT	70" X 44" STEEL RACK WITH MESH FLOOR	3813010M
	70" X 44" STEEL RACK WITHOUT MESH FLOOR	3813010
	70"X 44" ALLOY RACK WITH MESH FLOOR	4913010M
	70" X 44" ALLOY FLAT RACK	4913020M
	70" X 44" STEEL FLAT RACK	3813030
	70" X 49" TOURING RACK TO SUIT ARB ROOF TOP TENT	3813200
2003-09	FITTING KIT FOR 70" X 44" RACKS	3722010
2010-CURRENT	FITTING KIT FOR 70" X 44" & TOURING RACK	3722020
OPTIONAL	HI-LIFT JACK AND SHOVEL HOLDER FOR ARB ROOF RACK	K6202
	DOUBLE JERRY CAN HOLDER (BOLTS TO ROOF RACK)	3500390*

* WORKS WITH MOST STEEL JERRY CANS. WILL NOT WORK WITH PLASTIC JERRY CANS

